



**GENERAL INFO**

**SEDIMENT REMOVAL FILTER CARTRIDGE**

**Polyspun Sediment Cartridges**

The PX Series are compatible with most liquids and are highly effective for sediment, rust, sand, silt, algae removal. PX cartridges have no chemical residues.

The economical Puretec PX Series cartridges are constructed from virgin polypropylene which is spun and melted simultaneously. This innovative technique means there is no centre core to restrict filter performance. Precise depth filtration is achieved through graded density construction.

**MATERIALS OF CONSTRUCTION**

- Filter Media                      Polypropylene
- Temperature Rating            4.4°C to 60°C

**FEATURES & BENEFITS**

- 3 times longer life than comparable cartridges
- Graded depth filtration
- Protects appliances and health with sediment free water
- Flows up to 180 litres/minute
- 2 diameter options – Standard, MaxiPlus™
- Temperature rating up to 60°C.

## SPECIFICATIONS AND PERFORMANCE DATA

	Ordering Code	Micron Rating	Size	Flow (Lpm)
5"	<b>PX055</b>	1	standard 2.5" x 5"	14
	<b>PX011</b>	1	standard 2.5" x 10"	27
	<b>PX051</b>	5	standard 2.5" x 10"	28
	<b>PX101</b>	10	standard 2.5" x 10"	32
	<b>PX201</b>	20	standard 2.5" x 10"	34
10"	<b>PX501</b>	50	standard 2.5" x 10"	38
	<b>PX011-2</b>	1	standard 2.5" x 10"	27
	<b>PX051-2</b>	5	standard 2.5" x 10"	28
	<b>PX101-2</b>	10	standard 2.5" x 10"	32
	<b>PX201-2</b>	20	standard 2.5" x 10"	34
20"	<b>PX501-2</b>	50	standard 2.5" x 10"	38
	<b>PX012</b>	1	standard 2.5" x 20"	54
	<b>PX052</b>	5	standard 2.5" x 20"	56
	<b>PX102</b>	10	standard 2.5" x 20"	64
	<b>PX202</b>	20	standard 2.5" x 20"	67
10" MP	<b>PX502</b>	50	standard 2.5" x 20"	72
	<b>PX01MP1</b>	1	MaxiPlus 4.5" x 10"	75
	<b>PX05MP1</b>	5	MaxiPlus 4.5" x 10"	76
	<b>PX20MP1</b>	20	MaxiPlus 4.5" x 10"	84
20" MP	<b>PX50MP1</b>	50	MaxiPlus 4.5" x 10"	90
	<b>PX01MP2</b>	1	MaxiPlus 4.5" x 20"	152
	<b>PX05MP2</b>	5	MaxiPlus 4.5" x 20"	156
	<b>PX20MP2</b>	20	MaxiPlus 4.5" x 20"	164
	<b>PX50MP2</b>	50	MaxiPlus 4.5" x 20"	180

