



GENERAL INFO

MAXIPLUS™ STAINLESS STEEL HOUSINGS

The Puretec SS MaxiPlus™ are ideal for large scale commercial and industrial applications.

The Puretec SS MaxiPlus™ Series housings are suitable for the most demanding applications such as high pressure, temperature or corrosive, harsh conditions. The housings are capable of temperatures up to 99°C at 2,070 kPa and a maximum flow of 180 litres per minute.

HOUSING SPECIFICATIONS

- Material of Construction 304 stainless steel
- Connection BSP thread
- Filter Cartridge 10" or 20" x 4.5"
Double open end cartridges not included
- O-Ring Buna-N
- Maximum Temperature 99°C
- Maximum Pressure 2,070 kPa
- Application Suitable for industry and other relative water treatment

FEATURES & BENEFITS

- Large diameter for high flow rates.
- High pressure and temperature applications.
- Suitable for harsh and corrosive conditions.
- Polished 304 stainless steel construction.
- Heavy duty units for large scale commercial/industrial applications.

PERFORMANCE DATA

Model	Description	Housing Size (inches)	Connection Size	Max. Flow (Lpm)
SS25MP1	304 Stainless steel head and housing	10"	1"	90
SS40MP2	304 Stainless steel head and housing	20"	1½"	180

Note: Each housing includes a spanner tool, a mounting bracket kit and drain plug. For warm or hot water applications, we strongly recommend to test the chloride level in the water source & confirm suitability with the Puretec team.