



See Filter Housing dimensions below

GENERAL INFO

STAINLESS STEEL FILTER HOUSINGS

The Puretec UFC Series stainless steel filter housings offers a variety of solution for your large scale, heavy-duty filtration needs. Simple to install and maintain, these housings are ideal for schools, restaurants, farms, institutions and industrial use.

Holding from 7 to 28 cartridges, Puretec UFC Series housings provide flow rates from 132-1,400 Lpm. Housings are constructed of 304 or 316 stainless steel. Puretec UFC Series housings are compatible with a complete range of filter cartridges adding to their versatility.

HOUSING SPECIFICATIONS AND PERFORMANCE DATA

Model	Description	Connection Size	Dimensions (mm)				Max. Flow (Lpm)
			A	B	C	D	
UFC716C	Multi-cartridge 316 s/steel (Accepts 7 X 10" Cartridges)	2"	590mm	285mm	125mm	230mm	350
UFC726C	Multi-cartridge 316 s/steel (Accepts 7 X 20" Cartridges)	2"	890mm	285mm	125mm	230mm	700
UFC736C	Multi-cartridge 316 s/steel (Accepts 7 X 30" Cartridges)	2"	1110mm	285mm	125mm	230mm	1050
UFC746C	Multi-cartridge 316 s/steel (Accepts 7 X 40" Cartridges)	2"	1380mm	285mm	125mm	230mm	1400
UFC714C	Multi-cartridge 304 s/steel (Accepts 7 X 10" Cartridges)	2"	590mm	285mm	125mm	230mm	350
UFC724C	Multi-cartridge 304 s/steel (Accepts 7 X 20" Cartridges)	2"	890mm	285mm	125mm	230mm	700
UFC734C	Multi-cartridge 304 s/steel (Accepts 7 X 30" Cartridges)	2"	1110mm	285mm	125mm	230mm	1050
UFC744C	Multi-cartridge 304 s/steel (Accepts 7 X 40" Cartridges)	2"	1380mm	285mm	125mm	230mm	1400
UFC 7-OR	Multi-cartridge 7 round O-ring replacement	-	-	-	-	-	-

MATERIALS OF CONSTRUCTION

- Material SS304 or SS316
- Maximum Temperature 99°C
- Maximum Pressure 690 kPa

APPLICATIONS

- Highflow
- Commercial
- Industrial
- Reverse Osmosis Prefiltration

FEATURES & BENEFITS

- Heavy duty units for large scale commercial/ industrial applications
- Polished 304/316 stainless steel construction
- Accepts complete range of standard double open end (DOE) cartridges