Z1-T6


Quick Twist Undersink Filter System with Tripla™ 3-Way Mixer Tap









Tripla™ T6 3-Way Mixer Tap







Note: All dimensions are in mm

Specifications

Ordering Code	Temp °C	Pressure kPa	Flow (Lpm)	Micron Rating (nominal)	Connection	Cartridge Size	Capacity
Z1-T6	0-38	172-520	5.5	0.1	1/2" BSP x 1/4" Tube	10"	30,000L
Tripla™ T6	0-60	50-500	5	-	1/2" and 1/4" braided hose		

Notes

Wels Rating = 5 Stars. Replacement cartridge code: Z1-R. Required tap hole: 33mm.

Designed to filter mains and town water supply. On high pressure areas where the pressure exceeds the recommended working pressure as indicated, pressure limiting valves must be installed or warranty is voided

Warranty:

Tripla warranty is 1 year parts and labour, plus 5 years parts only. Puretec Z1 $\,$ Filter Systems Warranty is 1 year parts and labour, plus 9 years parts only. Excludes cartridges. Use only genuine Puretec replacement cartridge.







For more information contact your local stockist or visit us at **puretecgroup.com** Australia 1300 140 140 | New Zealand 0800 130 140



r can be made based on the specifications and images in this document. The design, technology, colours, features and prices are subject to change ment and all its contents are copyright protected. All rights are reserved, particularly alteration, translation and reproduction using electronic systen es in this document core parts for the period stated and include cover for parts and labour for the first year where applicable, subject to approval tration Specialists can provide you with advice to suit your needs.

